

APP CRS

057°

Rwy Idg

5500

TDZE

861

Apt Elev

882

RNAV (GPS) RWY 6

ATLANTA SPEEDWAY (HMP)

RNP APCH.

NA

When local altimeter setting not received, use Hartsfield-Jackson Atlanta Intl altimeter setting and increase all MDA 60 feet; increase LNAV Cats C/D visibility ¼ mile and Circling Cat D visibility ¼ mile. Straight-in Rwy 6 NA at night, Circling Rwy 6 NA at night. Rwy 6 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 3000 direct HAMPP and on track 122° to HUSKY and hold.

AWOS-3 124.825	ATLANTA APP CON 128.575 343.675	CLNC DEL 128.575 343.675	UNICOM 122.725 (CTAF) 0
-------------------	------------------------------------	-----------------------------	----------------------------

The main chart displays the RNAV (GPS) RWY 6 approach. Key features include:

- Altitudes:** 1465, 1391, 1207, 1246, 1061, 1062, 1039±, 1422, 2500 (6.5), 3000 NoPT (17.3), 266° (27.6).
- Navigation Aids:** HAMPP, HUSKY, ZUXUD (1.6 NM to RW06), BGGOH (FAF), JUPEP (IF/IAF), TIROE (IAF), BOWLIN (IAF).
- Angles:** 057°, 237°, 122°, 266°.
- Distances:** 4 NM, 2.5 NM (MSA RW06), 3.00° TCH 44, 6.5 NM, 3.4 NM, 1.6 NM.
- Procedure NA for arrival at BOWLIN on V97 southbound.**
- MISSED APCH FIX:** HUSKY, 4 NM, 131°, 31°.

4 NM Holding Pattern				
JUPEP				
3000				
237°				
057°				
057°				
2500				
BGGOH				
3.00° TCH 44				
ZUXUD 1.6 NM to RW06				
RW06				
1400				
6.5 NM				
3.4 NM				
1.6 NM				
CATEGORY	A	B	C	D
LNAV MDA	1300-1	439 (500-1)	1300-1¼	439 (500-1¼)
CIRCLING	1380-1	498 (500-1)	1700-2½ 818 (900-2½)	1740-2¾ 858 (900-2¾)

ELEV 882

TDZE 861

5500 X 75

0.5° UP

057° to RW06

MIRL Rwy 6-24 0

HAMPTON, GEORGIA

Amdt 2A 10SEP20

ATLANTA SPEEDWAY (HMP)

RNAV (GPS) RWY 6

33°23'N-84°20'W