

ILS or LOC RWY 22

LOC I-CVS 109.7	APCH CRS 218°	Rwy Idg 10,003 TDZE 4295 Arprt Elev 4295	AL-512 [USAF]	CANNON AFB (KCVS)
---------------------------	-------------------------	---	---------------	-------------------

*** When ALS inop, increase RVR to 40 and vis to ¾ miles.**
**** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1½ miles.**

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	CANNON TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
----------------------------	--	-------------------------------------	-------------------------------	----------------------------------

CAUTION:
 1. ILS Rwy 22 Height Group 4 WCH 19 feet.

Missed approach requires use of RNAV or ATC RADAR monitoring.

EMERG SAFE ALT 100 NM 8000

6000 CVS R-220	JEBES CVS R-220 [6]	7000	CLINK CVS R-193 [12]	VGSI and ILS glidepath not coincident (VGSI angle 3.00/TCH 38)
-------------------	-------------------------------	------	--------------------------------	--

CATEGORY	A	B	C	D	E
S-ILS 22*	4495/24				
S-LOC 22**	4720/24	425 (500-½)	4720/40 425 (500-¾)		
CIRCLING	4840-1 545 (600-1)	4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)	

ELEV 4295 TDZE 4295

218° 4 NM from FAF

REIL all Rwy HIRL all Rwy

FAF to MAP 4 NM					
Knots	60	90	120	150	180
Min:Sec	4:00	2:40	2:00	1:36	1:21