

ILS or LOC RWY 4

LOC I-GLO
108.5
APCH CRS
038°

Rwy Idg **10,003**
TDZE **4284**
Arprt Elev **4295**
AL-512 [USAF]
CANNON AFB (KCVS)

⚠ *When ALS inop, increase all CAT RVR to 40 and vis to ¾ miles.
****** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
CAT CDE RVR to 60 and vis to 1½ miles.

ALSF-1

† MISSED APPROACH: Climb to 6000 out CVS TACAN R-036 to 5 DME (FETEP) turning left climb to 7000 inop CVS R-003 to 12 DME (HEDOB) and hold.

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	CANNON TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
----------------------------	--	-------------------------------------	-------------------------------	----------------------------------

CANNON Chan 53 CVS

LOCALIZER 108.5
I-GLO

Max holding alt 10,000
Min holding alt 7000

Max holding alt 10,000
Min holding alt 7000

† Missed approach requires use of RNAV or ATC radar monitoring.

ATC RADAR OR DME REQUIRED

EMERG SAFE ALT 100 NM 9000

ELEV 4295	TDZE 4284
-----------	-----------

CATEGORY	A	B	C	D	E
S-ILS 4 *	4484/24		200	(200-½)	
S-LOC 4 **	4680/24	396 (400-½)	4680/35	396 (400-¾)	
C CIRCLING	4840-1 545 (600-1)	4860-1½	5000-2¼	5020-2½	
		565 (600-1½)	705 (800-2¼)	725 (800-2½)	

REIL all Rwy
HIRL all Rwy

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44