

WAAS CH 81830 W17A	APP CRS 173°	Rwy Idg 12000 TDZE 5339 Apt Elev 5434
--	------------------------	--

RNAV (GPS) Y RWY 17L

DENVER INTL (DEN)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 48°C (119°F). DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. For inoperative MALS R increase LNAV Cats C/D visibility to RVR 5500. Use of FD or AP providing RNAV track guidance required during simultaneous operations. Simultaneous approach authorized with Rwy 16L/16R and 17R.
RVR 1800 authorized with use of FD or AP or HUD to DA.

MALS R

MISSED APPROACH: Climb to 5900 then climbing left turn to 10000 direct LIMEX and hold.

D-ATIS ARR 125.6 379.9 DEP 134.025	DENVER APP CON 119.3 307.3 120.35 379.3 (NORTH) (SOUTH)	DENVER TOWER 132.35 239.275	GND CON 121.85 377.1	CLNC DEL 118.75	CPDLC
--	--	---------------------------------------	--------------------------------	---------------------------	-------

RADAR REQUIRED

Λ 6260

9000

173°

(3.7)

9000

(2.6)

8000

(3.2)

7000

(3.2)

(IF) GWENS

GRIFS

HALTR

HHOLT

(FAF) IRINE

5482

RW17L

MISSED APCH FIX

LIMEX

261°

7 NM

ELEV 5434	D	TDZE 5339
-----------	----------	-----------

173° to RW17L

HIRL all Rwys

TDZ/CL Rwys 7, 16L, 16R, 17R, 26, 34L, 34R, 35L, 35R

5900	10000	LIMEX	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 66).			
*LNAV only		*1 NM to RW17L				
IRINE		HHOLT	HALTR	GRIFS	GWENS	
7000		8000	9000	9000	9000	GP 3.00° TCH 48
1 NM		4.1 NM	3.2 NM	3.2 NM	2.6 NM	3.7 NM
CATEGORY		A	B	C	D	
LPV DA #		5539/24 200 (200-½)				
LNAV/VNAV DA		5648/24 309 (300-½)				
LNAV MDA		5700/24 361 (300-½)		5700/35 361 (300-½)		

DENVER, COLORADO
Amdt 1B 07DEC17

39°52'N-104°40'W

DENVER INTL (DEN)

RNAV (GPS) Y RWY 17L

SW-1, 31 DEC 2020 to 28 JAN 2021

SW-1, 31 DEC 2020 to 28 JAN 2021