

WAAS CH 86299 W25A	APP CRS 256°	Rwy Idg 5500 TDZE 44 Apt Elev 45
--	------------------------	---

RNAV (GPS) RWY 25

OXNARD (OXR)

⚠

Inoperative table does not apply. Baro-VNAV NA when using Camarillo altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). DME/DME RNP -0.3 NA. When local altimeter setting not received, use Camarillo altimeter setting and increase all DA 18 feet, all MDA 20 feet, and Circling Cat D visibility ¼ mile. Helicopter visibility reduction below ¾ SM NA.

MALSF

MISSED APPROACH: Climb to 2000 direct PEWKI and on track 239° to SQUID and hold.

ATIS 118.05	POINT MUGU APP CON* 124.7 335.5	OXNARD TOWER* 134.95 (CTAF) 257.8	GND CON 121.9
-----------------------	---	---	-------------------------

ELEV 45	D	TDZE 44
---------	----------	---------

2000

PEWKI

tr 239°

SQUID

*LNAV only

RW25

CUKUM 5.1 NM to RW25

NELLY 3200

HUPLA 3700

CUDAK 4200

GP 3.00° TCH 58

5.1 NM

4.6 NM

3 NM

3.4 NM

CATEGORY	A	B	C	D
LPV DA	294-1 250 (300-1)			
LNAV/VNAV DA	333-1 289 (300-1)			
LNAV MDA	520-1 476 (500-1)		520-1 ³ / ₈ 476 (500-1 ³ / ₈)	
CIRCLING	520-1 475 (500-1)		520-1 ¹ / ₂ 700-2 475 (500-1 ¹ / ₂) 655 (700-2)	

REIL Rwy 7

MIRL Rwy 7-25

OXNARD, CALIFORNIA

Amtd 1B 31MAR16

34°12'N-119°12'W

OXNARD (OXR)

RNAV (GPS) RWY 25